

111-01128

HellermannTyton



Article Number: 111-01128

Description: High-Temp Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66HIRHSUV, Black, 1000/pkg

Base Data	
Local Order Number	111-01128
Type	T50L
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • High impact, heat and UV stabilized cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration. • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
GLOBAL PART NAME	T50L-PA66HIRHSUV-BK
Short Description	High-Temp Cable Tie, 15.35" Long, UL Rated, 50lb Tensile Strength, PA66HIRHSUV, Black, 1000/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0lbs
Minimum Tensile Strength (Metric)	225.0N
Length L (Imperial)	15.35"
Length L (Metric)	390.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.19"
Width W (Metric)	4.8mm
Bundle Diameter Min. (Imperial)	0.06"

111-01128



Product Dimensions	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	4.3"
	Bundle Diameter Max. (Metric)	109.2mm
	Thickness T (Metric)	1.4mm
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
UL Recognized (US)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces