

111-01752

HellermannTyton



Article Number: 111-01752

Description: Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, PA12, Black, 25/bag

| | | |
|--------------------|-------------------------------------|--|
| Base Data | | |
| | Local Order Number | 111-01752 |
| | Type | T150M |
| | Color | Black (BK) |
| | Features and benefits | <ul style="list-style-type: none"> • Engineered and manufactured for maximum performance and quality. • Made from 100% high-quality plastic to ensure efficient recycling. • Inside serration for a strong hold onto bundles. • Easy application either manually or with a processing tool. • Bent tail allows for simpler insertion. |
| | Quantity Per | bag |
| | Product Description | Heavy-Duty T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. The bent tail allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
| | GLOBAL PART NAME | T150M-PA12-BK |
| | Short Description | Heavy Duty Cable Tie, 21" Long, UL Rated, 175lb Tensile Strength, PA12, Black, 25/bag |
| Product Dimensions | | |
| | Minimum Tensile Strength (Imperial) | 175.0lbs |
| | Minimum Tensile Strength (Metric) | 780.0N |
| | Length L (Imperial) | 21.0" |
| | Length L (Metric) | 530.0mm |
| | Fixation Method | None |
| | Identification Plate Position | none |
| | Releasable Closure | No |
| | Tie Closure | plastic pawl |
| | Variant | Inside Serrated |
| | Width W (Imperial) | 0.35" |
| | Width W (Metric) | 8.9mm |
| | Cable Tie Width Max. (Imperial) | .35" |

111-01752



| | | |
|-----------------------------|---------------------------------|----------------------------------|
| Product Dimensions | Cable Tie Width Max. (Metric) | 8.9mm |
| | Height H (Imperial) | 14.0" |
| | Height H (Metric) | 355.60mm |
| | Bundle Diameter Min. (Imperial) | 0.32" |
| | Bundle Diameter Min. (Metric) | 8.0mm |
| | Bundle Diameter Max. (Imperial) | 5.9" |
| | Bundle Diameter Max. (Metric) | 150.0mm |
| | Thickness T (Metric) | 1.9mm |
| Material and Specifications | | |
| | Material | Polyamide 12 (PA12) |
| | Material Shortcut | PA12 |
| | Flammability | UL 94 HB |
| | Halogenfree | Yes |
| | Operating Temperature | -40°F to +203°F (-40°C to +95°C) |
| | ROHS Compliant | Yes |
| | UL Recognized (US and Canada) | Yes |
| | UL Recognized (US) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 25 |
| | Package Quantity (Metric) | 25 |
| | Customs Number(Schedule B) | 3926909987 |