

111-25300

HellermannTyton



Article Number: 111-25300

Description: Heavy Duty Cable Tie, 22" Long, UL Rated, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg

Base Data	
Local Order Number	T255M0HIRX2
Type	T255M
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> • High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
GLOBAL PART NAME	T255M-PA66HIRHSUV-BK
Short Description	Heavy Duty Cable Tie, 22" Long, UL Rated, 250lb Tensile Strength, PA66HIRHSUV, Black, 25/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	250.0lbs
Minimum Tensile Strength (Metric)	1115.0N
Length L (Imperial)	22.0"
Length L (Metric)	560.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Variant	Inside Serrated
Width W (Imperial)	0.50"
Width W (Metric)	12.7mm
Bundle Diameter Min. (Imperial)	0.49"
Bundle Diameter Min. (Metric)	12.5mm
Bundle Diameter Max. (Imperial)	6.3"

111-25300



Product Dimensions	Bundle Diameter Max. (Metric)	160.0mm
Material and Specifications	Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
	Material Shortcut	PA66HIRHSUV
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +230°F (-40°C to +110°C)
	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
	UL Recognized (US)	Yes
Logistic and Packaging	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces