

904-00359



Article Number: 904-00359

Description: Convoluted Tubing, Slit, 1" Dia, PEUV, Black with Orange Stripe, 2250ft/carton

Base Data	
Local Order Number	904-00359
Type	CTPUV10
Color	Black with Orange Stripe (BKSTOG)
Features and benefits	<ul style="list-style-type: none"> • Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install. • Tubing provides full coverage where spiral wrap or other coverings may not be suitable. • In harsh applications the tubing provides resistance to crushing, impact, and abrasion. • Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.
Quantity Per	carton
Product Description	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
GLOBAL PART NAME	CTPUV10-PEUV-BK
Short Description	Convoluted Tubing, Slit, 1" Dia, PEUV, Black with Orange Stripe, 2250ft/carton
Product Dimensions	
Length L (Imperial)	2250.0ft
Length L (Metric)	685.8m
Diameter D (imperial)	1.32"
Diameter D (metric)	33.53mm
Diameter D2 (imperial)	1.06"
Diameter D2 (metric)	26.92mm
Outside Diameter D (imperial)	1.32"
Outside Diameter OD (metric)	33.53mm
Nominal Diameter (Imperial)	1"

904-00359



Product Dimensions	Nominal Diameter (Metric)	25.4mm
	Wall Thickness WT (Imperial)	0.006"
	Wall Thickness WT (Metric)	0.152mm
Material and Specifications	Material	Polyethylene, UV-resistant (PEUV)
	Material Shortcut	PEUV
	Flammability	UL 94 HB
	Halogenfree	Yes
	Operating Temperature	-40°F to +199°F (-40°C to +93°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging	Package Quantity (Imperial)	2250ft
	Package Quantity (Metric)	685.80m
	Customs Number(Schedule B)	3926909987