

156-00875

Article Number: 156-00875

Description: Cable Tie & Edge Clip, 6.0" Long, EC22, Panel Thickness .04"-.12", 50lb, PA66HS, Black, 500/bag



Base Data	Local Order Number	156-00875
	Type	T50SOSEC22
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> • Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole. • Edge Clip provides low insertion force and high extraction force ideal for assembly environments. • Two piece assembly allows the mount to slide along the strap ensuring proper orientation. • Cable tie is outside serrated to reduce bundle chafing.
	Quantity Per	bag
	Product Description	The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.
	GLOBAL PART NAME	T50SOSEC22-PA66HS/PA66HIRHS-BK
	Short Description	Cable Tie & Edge Clip, 6.0" Long, EC22, Panel Thickness .04"-.12", 50lb, PA66HS, Black, 500/bag
	Product Dimensions	
	Minimum Tensile Strength (Imperial)	50.0lbs
	Minimum Tensile Strength (Metric)	225N
	Length L (Imperial)	6.0"
	Length L (Metric)	150.0mm
	Length L2 (Imperial)	0.59"
	Fixation Method	EdgeClip, sideways, assembled, 2 piece
	Identification Plate Position	none
	Length L2 (Metric)	15.0mm
	Releasable Closure	No
	Variant	Outside Serrated
	Width W (Imperial)	0.18"

156-00875



Product Dimensions	Width W (Metric)	4.6mm
	Width W2 (Imperial)	0.36"
	Width W2 (Metric)	9.2mm
	Height H (Imperial)	.05"
	Height H (Metric)	1.30mm
	Height H2 (Imperial)	.50"
	Height H2 (Metric)	12.70mm
	Bundle Diameter Min. (Imperial)	0.04"
	Bundle Diameter Min. (Metric)	1.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.0mm
	Panel Thickness Min. (Imperial)	0.04"
	Panel Thickness Min. (Metric)	1.0mm
	Thickness T (Imperial)	0.05"
	Thickness T (Metric)	1.3mm
Material and Specifications		
	Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HS PA66HIRHS PA66HIRHS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Weight (Metric)	2.7kg