

Specification Sheet

Part Number: 157-00421



Article Number

157-00421

Type

T50ROSFT5.6SO25R

Color

Black (BK)

Features & Benefits

- HIRHSUV cable ties provide excellent resistance to UV, chemical and moisture sensitive environments.
- Can be preinstalled on site to reduce installation labor and offset design feature reduces potential for abrasion.
- First Solar vetted design

Quantity Per

3000 bag

Product Description

HellermannTyton's Series 6 Solar Tie features a head design specifically tailored for First Solar Series 6 module which can be pre-installed. The bent tail design allows quick and simple installations by hand.

Short Description

Series 6 Solar Tie, 50lb Tensile Strength, HIRHSUV, Black, 3000/pkg

Global Part Name

T50ROSFT5.6SO25R-HIRHSUV-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225.0

Length L (Imperial)

8.0

Length L (Metric)

202.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Outside Serrated

Width W (Imperial)

0.19

Width W (Metric)

5.08

Bundle Diameter Min (Imperial)

0.13

Bundle Diameter Min (Metric)

1.8

Bundle Diameter Max (Imperial)

1.97

Bundle Diameter Max (Metric)

50

Thickness T (Metric)

1.5

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
ROHS Complaint	Yes