




EXTERNAL TOOTH K-LOCK

STEEL & STAINLESS



"K" LOCK NUTS

SHAKEPROOF*
#501-01

Nominal Size or Basic Thread Diameter		F			G		H1		I	
		Width Across Flats			Width Across Corners		Nut Thickness		Washer Diameter	
		Basic	Max	Min	Max	Min	Max	Min	Max	Min
4	0.112	1/4	0.250	0.241	0.289	0.275	0.098	0.087	0.286	0.277
5	0.125	5/16	0.312	0.302	0.361	0.344	0.114	0.102	0.348	0.338
6	0.138	5/16	0.312	0.302	0.361	0.344	0.114	0.102	0.348	0.338
6 SP	0.138	1/4	0.250	0.241	0.289	0.275	0.098	0.087	0.287	0.277
8	0.164	11/32	0.344	0.332	0.397	0.378	0.130	0.117	0.381	0.370
8 SP	0.164	5/16	0.312	0.302	0.361	0.344	0.114	0.102	0.381	0.338
10	0.190	3/8	0.375	0.362	0.433	0.413	0.130	0.117	0.406	0.395
12	0.216	7/16	0.438	0.423	0.505	0.482	0.161	0.148	0.506	0.494
1/4	0.250	7/16	0.438	0.423	0.505	0.482	0.193	0.178	0.506	0.494
5/16	0.313	1/2	0.500	0.489	0.577	0.557	0.273	0.258	0.592	0.579
3/8	0.375	9/16	0.562	0.551	0.650	0.628	0.337	0.320	0.665	0.651
1/2	0.500	3/4	0.750	0.736	0.866	0.840	0.437	0.425	0.898	0.878

"SP" denotes a "small pattern" across the flats.

*Shakeproof standard #501-01 does not specify dimensions for the #5, #8 SP and 1/2" diameters.

Description	A hex nut pre-assembled with a free spinning external tooth lock washer. The locking action is achieved when the nut is tightened against a bearing surface as the teeth of the lock washer dig into it.
Applications/ Advantages	This is the most popular type of locknut because of its versatility, cost and ease of installation. Doesn't gall screw threads.
Material	Steel: Nuts-- AISI 1008-1020 or equivalent steel; Washers-- 1050-03 or equivalent steel. Stainless: Nuts-- One of the following austenitic alloys: 302, 303, 303Se, 304, XM7; Washers-- 420 stainless.
Hardness	Steel: Washers-- Rockwell C38 minimum, C44 maximum Stainless: Washers-- Rockwell C40 - 50
Plating	See Appendix-A for information about the plating of steel nuts.

*Shakeproof is the original writer of K-lock nut specifications.